

	SEL-32 (basic)	SES-32 (brief)
Ratedvoltage	230VAC	230VAC
The max output current	32A	32A
Operatingfrequency	50Hz/60Hz	50Hz/60Hz
The max output power	7.2KW	7.2KW
Chargeand controlway	IC card/APPQR cord	IC card/chargewhen insert
Human-computer interaction	LCD touchscreen(5/8cun)	LED screen
IC card	ISO 14443A	ISO 14443A
Standby power consumption	5W	2W
Communication mode	GPRS/WiFi (optional)	GPRS/WiFi (optional)
EMI	CISPR22/EN55022 CLASS B	CISPR22/EN55022 CLASS B
EMS	EN 61000-4-5 ±2KV/±4KV perf. CriteriaB	EN 61000-4-5 ±2KV/±4KV perf. CriteriaB
Executivestandard	EN 61851-1	EN 61851-1
ProtectionLevel	IP55(storage) IP54(Matedwith vehicle)	IP55(storage) IP54(Matedwith vehicle)
Temperature/Humidity	-30-50°C /5%-95%(non-conde nsate)	-30-50°C /5%-95%(non-conde nsate)
Altitude	<2000m	<2000m
ProductWeight	8Kg	6Kg
ProductSize	314mm×454mm×135mm	237mm×343mm×115mm
Installation	Pedestal/wall installation	Pedestal/wall installation



Caution! The use of product is must matched up A model RCCB(2P-40A,30mA electric leakage, A model RCCB).

Before assembly, please confirm the materials complete, do not assemble if the material lack.

### Transportation and storage

The product is packed well before leave factory. Avoid sharp pounding, jolt and damage the package when transport. The storage and transportation temperature is -40°C+70°C, the humidity is 95%, the ambient air shouldn't contain acidity, alkalinity and other corrosive gas or explosive gas.



dangerous!

Itismaydamaged the device due to the improper transportation!